92x92x25 mm


39.5~55.0 CFM



Specifications


Model	Bearing ◒ 2BALL ○ Sleeve	Rating Voltage (VDC)	Power Current (mA)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (inch-H_2O)	Noise (dB(A))	Weight (g)	Curve
EE92251BX-000U-A99	◒	12	190	2.30	3400	55.0	0.21	37.5	89.0	1
EE92251B1-000U-A99	◒	12	165	2.00	3000	51.5	0.15	34.0	94.0	2
EE92251B2-000U-999	◒	12	135	1.60	2700	45.0	0.13	32.0	94.0	3
EE92251B3-000U-999	◒	12	105	1.30	2400	39.5	0.10	28.0	94.0	4
EE92252BX-000U-A99	◒	24	100	2.40	3400	55.0	0.21	37.5	89.0	1
EE92252B1-000U-A99	◒	24	87	2.10	3000	51.5	0.15	34.0	94.0	2
EE92252B2-000U-999	◒	24	70	1.70	2700	45.0	0.13	32.0	94.0	3
EE92252B3-000U-999	◒	24	57	1.40	2400	39.5	0.10	28.0	94.0	4
EE92252S1-000U-A99	○	24	87	2.10	3000	51.5	0.15	34.0	94.0	2
EE92252S2-000U-999	○	24	72	1.70	2700	45.0	0.13	32.0	94.0	3
EE92252S3-000U-999	○	24	60	1.40	2400	39.5	0.10	28.0	94.0	4


Air Flow-Static Pressure Characteristics



*All model could be customized. Please contact with Sunon Sales

External dimensions(mm)





Beijing Hengrui Mechanical and Electrical Equipment Co,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

92x92x25 mm


28.4 CFM




Specifications


MAGLev by SUNON	Bearing	Rating Voltage	Power Current	Power Consumption	Speed	Air Flow	Static Pressure	Noise	Weight	Curve
	● VAPO	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H_2O)	(dB(A))	(g)	
HA92251V4-1000U-A99	●	12	45	0.54	1700	28.4	0.05	17.7	92.0	1


Air Flow-Static Pressure Characteristics



External dimensions(mm)







*All model could be customized. Please contact with Sunon Sales

Beijing Hengrui Mechanical and Electrical Equipment Co,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

92x92x38 mm


91.7~120.2 CFM




Specifications

Model	Bearing	Rating Voltage	Power Current	Power Consumption	Speed	Air Flow	Static Pressure	Noise	Weight	Curve
	◐ 2BALL ○ Sleeve	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H_2O)	(dB(A))	(g)	
PMD1209PMB1-A (2).GN	◐	12	1040	12.5	4900	120.2	0.71	57.6	190.0	1
PMD1209PMB2-A (2).GN	◐	12	710	8.5	4400	106.3	0.56	53.8	190.0	2
PMD1209PMB3-A (2).GN	◐	12	470	5.6	3800	91.7	0.43	50.3	190.0	3
PMD2409PMB1-A (2).GN	◐	24	510	12.2	4900	120.2	0.71	57.6	190.0	1
PMD2409PMB2-A (2).GN	◐	24	400	9.6	4400	106.3	0.56	53.8	190.0	2
PMD2409PMB3-A (2).GN	◐	24	250	6.0	3800	91.7	0.43	50.3	190.0	3
PMD4809PMB1-A (2).GN	◐	48	240	11.5	4900	120.2	0.71	57.6	190.0	1
PMD4809PMB2-A (2).GN	◐	48	160	7.7	4400	106.3	0.56	53.8	190.0	2
PMD4809PMB3-A (2).GN	◐	48	120	5.8	3800	91.7	0.43	50.3	190.0	3

Air Flow-Static Pressure Characteristics



External dimensions(mm)



*All model could be customized. Please contact with Sunon Sales

Beijing Hengrui Mechanical and Electrical Equipment Co,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com