80x80x25 mm (IP68)

33.0~60.0 CFM




Specification

Model	Bearing	Rated Voltage	Power Current	Power Consumption	Speed	Airflow	Static Pressure	Noise	Weight	Curve
	● 2BALL ○ Sleeve	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H_2O)	(dB(A))	(g)	
GF80251B1-0000-AE9	●	12	330	3.96	4800	60.0	0.41	47.5	105.0	1
GF80251B2-0000-AE9	●	12	255	3.06	4500	57.0	0.35	46.0	105.0	2
GF80251B3-0000-AE9	●	12	200	2.40	4200	53.0	0.30	44.5	105.0	3
GF80251B5-0000-AE9	●	12	145	1.74	3200	41.0	0.18	33.0	87.0	4
GF80251B6-0000-AE9	●	12	120	1.44	2900	37.0	0.15	30.0	87.0	5
GF80251B7-0000-AE9	●	12	84	1.01	2600	33.0	0.11	28.0	87.0	6
GE80252B1-0000-AE9	●	24	200	4.80	4800	60.0	0.41	47.5	105.0	1
GE80252B2-0000-AE9	●	24	166	3.99	4500	57.0	0.35	46.0	105.0	2
GE80252B3-0000-AE9	●	24	137	3.29	4200	53.0	0.30	44.5	105.0	3
GF80252B5-0000-AE9	●	24	73	1.76	3200	41.0	0.18	33.0	87.0	4
GF80252B6-0000-AE9	●	24	59	1.42	2900	37.0	0.15	30.0	87.0	5
GF80252B7-0000-AE9	●	24	45	1.08	2600	33.0	0.11	28.0	87.0	6


Function


(Speed 1, 2, 3) R Type : FE9 ／ F Type : GE9 ／ PWM : HE9, QE9, SE9
(Speed 5, 6, 7) R Type : FE9 ／ F Type : GE9


Air Flow-Static Pressure Characteristics



External Dimensions(mm)







Beijing Hengrui Mechanical and Electrical Equipment Co,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

80x80x25 mm

45.0 CFM




Specification

Model	Bearing	Rated Voltage	Power Current	Power Consumption	Speed	Airflow	Static Pressure	Noise	Weight	Curve
	● 2BALL ○ Sleeve	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H_2O)	(dB(A))	(g)	
EF80251BX-10000-A99	●	12	122	1.47	3600	45.0	0.23	36.1	89.0	1
EF80252BX-10000-A99	●	24	71	1.71	3600	45.0	0.23	36.1	89.0	1


Function


R Type : F99 ／ F Type : G99 ／ PWM : H99, Q99, S99


Air Flow-Static Pressure Characteristics



External Dimensions(mm)







Beijing Hengrui Mechanical and Electrical Equipment Co,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com

80x80x25 mm (GR487)

33.0~41.0 CFM




Specification

Model	Bearing	Rated Voltage	Power Current	Power Consumption	Speed	Airflow	Static Pressure	Noise	Weight	Curve
	● 2BALL ○ Sleeve	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H_2O)	(dB(A))	(g)	
GF80251B5-0000-AD9	●	12	145	1.74	3200	41.0	0.18	33.0	87.0	1
GF80251B6-0000-AD9	●	12	120	1.44	2900	37.0	0.15	30.0	87.0	2
GF80251B7-0000-AD9	●	12	84	1.01	2600	33.0	0.11	28.0	87.0	3
GF80252B5-0000-AD9	●	24	73	1.76	3200	41.0	0.18	33.0	87.0	1
GF80252B6-0000-AD9	●	24	59	1.42	2900	37.0	0.15	30.0	87.0	2
GF80252B7-0000-AD9	●	24	45	1.08	2600	33.0	0.11	28.0	87.0	3


Function

R Type : FD9 ／ F Type : GD9

Air Flow-Static Pressure Characteristics



External Dimensions(mm)



Beijing Hengrui Mechanical and Electrical Equipment Co,Ltd
+86 10-62547612
zhangyu@bjhengrui.cn
en.bjhengrui.com